UHPC Bridge Deck Overlay in Sioux County, Iowa

Philipp Hadl, Ph.D.* (corresponding author) – UHPC Solutions, 433 Broadway – Suite 604, New York, 10013 NY, USA, (212) 691-4537, Email: <u>philipp.hadl@uhpcsolutions.com</u>

Marco Maurer – WALO International AG, Heimstrasse 1, 8953 Dietikon, Switzerland, +41 +41 31 941 21 21 228, Email: <u>marco.maurer@walo.com</u>

Gregory Nault – LafargeHolcim, 8700 W Bryn Mawr Ave, Ste 300, Chicago, IL 60631, 773-230-3069, Email: <u>gregory.nault@lafargeholcim.com</u>

Gilbert Brindley –UHPC Solutions, 433 Broadway – Suite 604, New York, 10013 NY, USA (844) 857 8472, Email: <u>gil.brindley@UHPCSolutions.com</u>

Ahmad Abu-Hawash – Iowa Department of Transportation, 800 Lincoln Way, Ames, IA 50010, 515-239-1393, Email: <u>Ahmad.Abu-Hawash@iowadot.us</u>

Dean Bierwagen – Iowa Department of Transportation, 4611 U.S. 75 N, Sioux City, IA 51108, 712-239-1367, Email: <u>Dean.Bierwagen@iowadot.us</u>

Curtis Carter – Iowa Department of Transportation, 4611 U.S. 75 N, Sioux City, IA 51108, 712-239-1367, Email: <u>Curtis.Carter@iowadot.us</u>

Darwin Bishop – Iowa Department of Transportation, 2800 Gordon Dr., P.O. Box 987, Sioux City, IA 51102, 712-274-5826, Email: <u>Darwin.Bishop@iowadot.us</u>

Dean Herbst – Iowa Department of Transportation, 4611 U.S. 75 N, Sioux City, IA 51108, 712-239-1367, Email: <u>Dean.Herbst@iowadot.us</u>

Sri Sritharan, Ph.D.–Professor, Iowa State University, 2711 S Loop Drive, Ames, Iowa 50010, Email : <u>sri@iastate.edu</u>

Primary Topic Area: Application/Projects

Secondary Topic Area: Bridges

Date Submitted: (10/17/2018)

Abstract

Ultra High Performance Concrete (UHPC) on bridges in the United States have typically been joint applications with limited deck overlay placements. Iowa Department of Transportation (DOT) let a pilot project for UHPC bridge deck overlay on a 205.5 ft x 44 ft Pretensioned Prestressed Concrete girder bridge on US 18 over the Floyd River in Sheldon, Iowa. The project has sufficient quantity to be the first machine

Second International Interactive Symposium on Ultra-High Performance Concrete

placed UHPC overlay in the United States. The existing bridge condition is suitable to test UHPC material placement as a repair and rehabilitation strategy.

The project required staged construction to maintain one lane of traffic at all times. The UHPC machine placement plan included a two-layer approach, different fiber percentages per layer and multiple passes to achieve 1 ³/₄" depth overlay. It addressed machine placement widths, minimized the number of steel fibers on the road surface, and compensated imperfections in the surface from the first layer.

The UHPC deck overlay pilot project revealed that the UHPC is a strong material that functions as a waterproofing element and increases the structural capacity as compared to conventional overlay mixes. Using a paving machine was intentionally overdesigned for this small bridge but demonstrated the feasibility of how efficiently the overlay can be deployed on larger structures. Required surface finish smoothness was achieved by conventional grinding technique and longitudinal grooving provided bridge deck texture. Due to the rapid hardening of the UHPC, the bridge was opened for traffic three days after the last placement.



Figure 1. UHPC Installation with paving machine